



货物运输条件鉴定书

Certification for Safe Transport of Goods

货物名称:	铅酸电池 12V7Ah
Goods name :	Lead acid battery 12V7Ah
委托单位:	广州市未绿能源科技有限责任公司
Consignor:	Future Green Technology Co.,Ltd.
运输 方式:	海运
Transportation :	Marine



Tel: +86-0755-33663308



声 明 Statement

1. 本公司依据《国际海运危险货物规则》(39-18 版)以及委托人(托运人或其他代理人)提供的物品及其运输信息,确定货物的航空运输条件并出具此鉴定书。

The certification is issued by SEM Test according to International Maritime Dangerous Goods Code (Amdt.39-18) and the information of the goods and the information of its shipping provided by the consignor (shipper of his agent).

2. 委托单位必须如实提供样品及资料,并保证申报品名和样品与运输货物相同。

The consignor should provide sample and relevant data, at the same time, they should guarantee the consistence of the product's name they declared, the samples they provided and the goods to be transported.

3. 本鉴定书的鉴定结论仅对委托单位提供的样品负责。

The conclusion of this certification is responsible for the sample provided by the consignor.

4. 本鉴定书经主检员、审核人和批准人签字并加盖本公司印章后生效。

This certification will be effective only after it is signed by the Appraiser, checker and approver, and stamped by SEM Test.

5. 未经本公司许可,不得部分复制、摘用本鉴定书内容。

This certification shall not be reproduced except in full, or extracted, without the written approval of SEM Test.

6. 鉴定书涂改无效。

The certification is invalid if it is blotted out.

7. 本鉴定书仅在本年度内有效。

This certification is only valid within the year.



货物名称 Goods name	中文 Chinese	铅酸电池 12V7Ah				
	英文 English	Lead acid battery 12V7Ah				
委托单位 Consignor		广州市未绿能源科技有限责任公司 Future Green Technology Co.,Ltd				
生产单位 Manufacturer		广州市未绿能源科技有限责任公司 Future Green Technology Co.,Ltd				
检查方法 Inspection method		《国际海运危险货物规则》(39-18 版) International Maritime Dangerous Goods Code (Amdt.39-18)			mdt.39-18)	
样品夕 Appears		黑色棱柱形电池,尺寸 151.6mm*107.3mm*66.2mm Black prismatic battery, size 151.6mm*107.3mm*66.2mm				
包装信息 Package information		电池数量 Battery number	6	包装件尺寸 Packaging dimensions	342*317*114mm	
		电池净重 net weight of batteries	11.8kg	包装件毛重 weight of the package	13kg	
电池信息 Battery information		类型 Type	铅酸电池 Lead acid battery			
		型号 Model	12V7Ah			
		额定能量 Nominal energy	84Wh			
		放置方式 Placement	只有电池 Battery only			

1. 该样品为阀控密封铅酸电池,已通过联合国《关于危险货物运输的建议书一标准与试验手册》附表部分 3.3 条款压差和震动测试。

This sample is Valve Control sealed lead-acid battery. Each battery is proved to meet the Requirements tests in the UN Manual of Tests and Criteria, ANNEX Part 3.3.

2. 根据特殊规定 238, 该物品不受 IMO IMDG Code 限制。

The article is not restricted to IMO IMDG Code according to special provision 238.

番注
Comments 毎个包装件都应贴有相关标识。
Each package should be labelled with a related handling label.

主检
Appraiser: 申核
Checker: 本第 批准
Approver:



_	业书编号 No.: WTX20X01000993B001
序号 No.	检查结果及其他事项 Inspection results and other things
1	本报告所述阀控密封铅酸电池无明显安全缺陷,不属于因安全原因召回的阀控密封铅酸电池。 Lithium cells and batteries listed in this report have no significant defect, and they are not the defective cells or batteries returned to the manufacturer for safety reasons.
2	本报告所述阀控密封铅酸电池已通过联合国《实验和标准手册》附表部分 3.3 小节相应测试要求,测试报告编号: WTX19X01001860B。 cells and batteries listed in this report are of the types proven to meet the requirements of each applicable test in the UN Manual of Tests and Criteria, ANNEX Part 3.3. test report number: WTX19X01001860B.
3	除安装在设备中外,电芯和电池须装在完全将其封闭的内包装内。电芯或电池须加以防护以免发生短路。这包括防止在同一包装内与可能导致短路的导电材料接触。内包装须装在符合 IMDG CODE 第 4.1.1.1、4.1.1.2 和 4.1.1.5 段规定的坚实的外包装内。 Cells and batteries, except when installed in equipment, shall be packed in inner packagings that completely enclose the cell or battery. Cells and batteries shall be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit. The inner packagings shall be packed in strong outer packagings which conform to the provisions of 4.1.1.1, 4.1.1.2, and 4.1.1.5.
4	安装在设备中的电芯和电池须加以保护以避免损坏和短路,该设备须配备有效的防止意外激活装置。如果电池安装在设备内,该设备须被包装在坚实的外包装内,该外包装由具有足够强度的材料建造并且设计与其容量的拟定用途相适应,除非内含这些电池的设备能够提供等效的保护。 Cells and batteries when installed in equipment shall be protected from damage and short circuit, and the equipment shall be equipped with an effective means of preventing accidental activation. When batteries are installed in equipment, the equipment shall be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained.
5	每批托运货物必须附带一份包括以下内容的文件: 标明包装件必须小心轻放,如果包装件损坏,有着火的危险。 标明如果包装件受到损坏,必须遵守的特别程序,包括检查和必要时重新包装。 应急电话号码。 Each consignment must be accompanied with a document with an indication that: The package must be handled with care and that a flammability hazard exists if the package is damaged Special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary A telephone number for additional information.



包装件内部和外部图片

The package photo











